

SECTION 1. Identification of the substance/preparation and of the company/undertaking

Manufacturer: E.I. du Pont de Nemours & Co.
 DuPont Performance Coatings
 Wilmington, DE, 19898

Telephone: Product information: (800) 441-7515
 Medical emergency: (800) 441-3637
 Transportation emergency: (800) 424-9300
 (CHEMTREC)

Product: **Isocyanate Activators, Hardeners, and Additives**

DOT Shipping Name: See DOT Addendum.

Hazardous Materials Information: See Section 10.

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
	64742-94-5	10.0	D 100.0 ppm A None O None
Aromatic hydrocarbon-B	64742-95-6	10.0@25.0°C	D 50.0 ppm A None O None
Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate	41556-26-7	None	A None O None
Bis(2,2,6,6, tetramethyl-4 piperidyl) sebacate	52829-07-9	None	S 1.0 mg/m3 A None O None
Butyl acetate	123-86-4	10.0	A 200.0 ppm 15 min STEL A 150.0 ppm O 150.0 ppm
Dibutyl tin dilaurate	77-58-7	0.2@160.0°C	A 0.2 mg/m3 15 min STEL Sn A 0.1 mg/m3 Sn O 0.1 mg/m3 Sn
Diisobutyl ketone	108-83-8	1.8	A 25.0 ppm O 50.0 ppm

Copyright 2007 E. I. duPont de Nemours and Company. All rights reserved. Copies may be made only for those using DuPont products.

SECTION 2. Composition/information on ingredients

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
1,2,4-trimethyl benzene	95-63-6	7.0@44.4°C	A 25.0 ppm O 25.0 ppm
1,6-hexamethylene diisocyanate	822-06-0	0.0@25.0°C	A 5.0 ppb O None
2,4,6- tri((dimethylamino)methyl) phenol	90-72-2	0.0@21.0°C	A None O None
2-ethylhexyl acetate	103-09-3	0.5	A None O None
2-methyl butyl acetate	624-41-9	None	A 100.0 ppm 15 min STEL A 50.0 ppm O None
4,6-dimethyl-2-heptanone	19549-80-5	None	A None O None
4-chlorobenzotrifluoride	98-56-6	7.6@25.0°C	D 20.0 ppm 8 & 12 hour TWA A None O None
Acetone	67-64-1	247.0@68.0°F	A 750.0 ppm 15 min STEL A 500.0 ppm O 1000.0 ppm D 500.0 ppm 8 & 12 hour TWA
Aliphatic polyisocyanate resin	28182-81-2	None	S 1.0 mg/m3 15 min STEL S 0.5 mg/m3 A None O None
Aromatic hydrocarbon-A			

Ethanol, 2-(2-butoxyethoxy)-	112-34-5	0.0	D 5.0 ppm A None O None
Ethyl 3-ethoxy propionate	763-69-9	1.1@25.0°C	A None O None
Ethyl acetate	141-78-6	93.2@25.0°C	A 400.0 ppm O 400.0 ppm
Ethylbenzene	100-41-4	7.0	A 125.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 25.0 ppm 8 & 12 hour TWA
Ethylene glycol monobutyl ether acetate	112-07-2	0.3	A 20.0 ppm D 20.0 ppm 8 & 12 hour TWA O None
Heptane	142-82-5	45.0@66.0°F	A 500.0 ppm 15 min STEL A 400.0 ppm O 500.0 ppm
Hexyl acetate isomers	88230-35-7	1.4	A 50.0 ppm O None
Isobutyl alcohol	78-83-1	9.7@22.0°C	A 50.0 ppm

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS	INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
Isophorone diisocyanate	4098-71-9	None	O 100.0 ppm A 5.0 ppb Skin O None	Propylene glycol monomethyl ether acetate	107-98-2	11.2@77.0°F	A 150.0 ppm 15 min STEL A 100.0 ppm O None
Isophorone diisocyanate homopolymer	53880-05-0	None	A None O None		108-65-6	3.8	D 10.0 ppm 8 & 12 hour TWA A None O None
Isopropyl alcohol	67-63-0	48.0	A 400.0 ppm 15 min STEL A 200.0 ppm O 400.0 ppm D 200.0 ppm 8 & 12 hour TWA	Salicylic acid	69-72-7	<0.0	O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust A None
Methyl acetate	79-20-9	171.3@68.0°F	A 250.0 ppm 15 min STEL A 200.0 ppm O 200.0 ppm	Siloxanes and silane esters	NotAvail	<1.0	A None O None
Methyl amyl ketone	110-43-0	3.4	A 50.0 ppm O 100.0 ppm	Substituted benzotriazole	25973-55-1	None	A None O None
Methyl ethyl ketone	78-93-3	71.2	A 300.0 ppm 15 min STEL A 200.0 ppm O 200.0 ppm D 300.0 ppm 15 min TWA D 200.0 ppm 8 & 12 hour TWA	Toluene	108-88-3	22.0	A 20.0 ppm
Methyl isobutyl ketone	108-10-1	15.1	A 75.0 ppm 15 min STEL A 50.0 ppm O 100.0 ppm	Trixylenyl phosphate	25155-23-1	1.0	O 300.0 ppm CEIL O 500.0 ppm 10 min TWA O 200.0 ppm D 50.0 ppm 8 & 12 hour TWA
N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1760-24-3	<1.0	A None O None	Vm&p naphtha	8032-32-4	17.9@68.0°F	A 300.0 ppm D 100.0 ppm O None
N-pentyl propionate	624-54-4	1.5	A None O None	Xylene	1330-20-7	8.0@25.0°C	A 150.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 150.0 ppm 15 min STEL D 100.0 ppm 8 & 12 hour TWA
Naphthalene	91-20-3	None	A 15.0 ppm CEIL Skin A 10.0 ppm Skin O 10.0 ppm D 0.1 ppm 8 & 12 hour TWA	*A=ACGIH, O=OSHA, D=DuPont, S=Suppliers. Limits are 8 hour TWA unless otherwise specified. Vapor pressure @ 20° C unless otherwise noted.			
P-toluenesulfonyl isocyanate	4083-64-1	0.0@50.0°C	A None O None	SECTION 3. Hazards identification			
Polyester resin	NotAvail	None	A None O None	Potential Health Effects:			
Primary amyl acetate	628-63-7	4.2	A 100.0 ppm 15 min STEL A 50.0 ppm O 100.0 ppm	Inhalation:			
Propylene glycol methyl ether				<p>May cause nose and throat irritation. May cause nervous system depression, characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product contains or is mixed with an isocyanate activator/hardener, the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung</p>			

function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion:

May result in gastrointestinal distress.

Skin or eye contact:

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Other Potential Health Effects in addition to those listed above:

4-chlorobenzotrifluoride

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: skin. Prolonged or repeated exposure may cause damage to any of the following organs/systems: kidneys, liver, thyroid. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Ingestion may cause any of the following: gastrointestinal irritation. Eye contact may cause any of the following: permanent eye injury. Inhalation may cause any of the following: stupor (central nervous system depression), respiratory tract irritation.

Acetone

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

Aliphatic polyisocyanate resin

Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure. The following medical conditions may be aggravated by exposure: asthma, skin disorders, respiratory disorders. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Skin or eye contact may cause any of the following: irritation.

Aromatic hydrocarbon-A

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Aromatic hydrocarbon-B

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate

Repeated exposure may cause allergic skin rash, itching, swelling.

Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate

Eye contact may cause any of the following: burns.

Butyl acetate

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

Diisobutyl ketone

The following medical conditions may be aggravated by exposure: asthma,

blood, dermatitis. Contact may cause skin irritation with discomfort or rash. Repeated exposure may cause allergic skin rash, itching, swelling. This substance may cause damage to any of the following organs/systems: eyes, kidneys, liver. Extremely high oral and inhalation doses in laboratory animals have shown weight changes in various organs such as the liver, kidney, brain, heart and adrenal gland. In addition liver and kidney injury were observed at the extremely high inhalation level. In another inhalation study there was a slight depression in the white blood cell count. Liquid or vapor causes irritation, experienced as stinging, excess blinking and tear production, with excess redness and swelling of the conjunctiva.

Ethanol, 2-(2-butoxyethoxy)-

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, kidneys, liver, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver. Recurrent overexposure may result in liver and kidney injury. High doses in laboratory animals have shown non specific effects such as irritation, weight loss, moderate blood changes. Eye contact may cause any of the following: severe irritation, burns, corneal injury.

Ethyl acetate

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

Ethylbenzene

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

Ethylene glycol monobutyl ether acetate

May destroy red blood cells. May cause abnormal kidney function. May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. The following medical conditions may be aggravated by exposure: central nervous system, gastrointestinal system, kidneys, liver, dermatitis. Can be absorbed through the skin in harmful amounts. Overexposure may cause damage to any of the following organs/systems: blood, kidneys, liver. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

Heptane

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, respiratory system, skin. May cause central nervous system effects such as dizziness, headache, nausea, and loss of consciousness. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Hexyl acetate isomers

May cause any of the following central nervous system effects: dizziness, headache.

Isobutyl alcohol

Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. May cause irritation of the mucous membranes. May cause abnormal liver function. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: bone marrow, liver. Prolonged skin contact may cause chemical burns. Liquid splashes in the eye may result in chemical burns.

Isophorone diisocyanate

Overexposure may cause damage to any of the following organs/systems: lungs, skin. The following medical conditions may be aggravated by overexposure: asthma, eczema, skin disorders, respiratory disorders.

Isophorone diisocyanate homopolymer

May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated and prolonged overexposure may cause delayed effects involving the respiratory system. Repeated overexposure to isocyanates may cause lung injury, including a decrease in lung function, which may be permanent. Overexposure may cause damage to any of the following organs/systems: lungs, skin. The following medical conditions may be aggravated by overexposure: asthma, eye disorders, eczema, skin disorders, respiratory disorders.

Isopropyl alcohol

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

Methyl ethyl ketone

Material is irritating to mucous membranes and upper respiratory tract. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, respiratory system, skin. Prolonged or repeated overexposure may cause any of the following: conjunctivitis, dermatitis. High concentrations have caused embryotoxic effects in laboratory animals. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

Methyl isobutyl ketone

The following medical conditions may be aggravated by exposure: asthma, respiratory disease, eye disorders, pulmonary conditions, skin disorders. Repeated or prolonged skin contact may cause any of the following: dryness, cracking of the skin, defatting. Inhalation may cause any of the following: dizziness, stupor (central nervous system depression), drowsiness, respiratory tract irritation.

N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane

May cause allergic skin reaction. Can produce skin sensitization in animals.

Naphthalene

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury.

WARNING: This chemical is known to the State of California to cause cancer.

P-toluenesulfonyl isocyanate

Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure. The following medical conditions may be aggravated by exposure: asthma, skin disorders, respiratory disorders. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Skin or eye contact may cause any of the following: irritation.

Propylene glycol methyl ether

Tests in laboratory animals have shown effects on any of the following organs/systems: kidneys, liver. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Propylene glycol monomethyl ether acetate

Recurrent overexposure may result in liver and kidney injury.

Salicylic acid

Individuals with preexisting diseases of the liver or kidneys may have increased susceptibility to the toxicity of excessive exposures. Skin permeation can occur in amounts capable of producing the effects of systemic toxicity.

Substituted benzotriazole

The following medical conditions may be aggravated by exposure: jaundice, liver disease. Repeated or prolonged ingestion may cause any of the following: changes in the blood, liver effects.

Toluene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

Trixylenyl phosphate

Has produced nervous system effects (such as weakness and tremors) in studies on laboratory animals.

Vm&p naphtha

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs, respiratory system, skin. This substance may cause damage to any of the following organs/systems: central nervous system, kidneys, liver, lungs, skin and eyes. Material may be harmful or fatal if swallowed.

Xylene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

SECTION 4. First aid measures

First Aid Procedures:

Inhalation:

If affected by inhalation of vapor or spray mist, move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulty persists, or occurs later, consult a physician.

Ingestion:

In the unlikely event of ingestion, DO NOT INDUCE VOMITING. Call a physician immediately and have names of ingredients available.

Skin or eye contact:

In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, contact a physician.

Other precautions:

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

SECTION 5. Fire-fighting measures

Flash Point (Closed Cup): See Section 11 for exact values.

Flammable Limits: LFL 0.5 % UFL 24.6 %

Extinguishing Media:

Universal aqueous film-forming foam, carbon dioxide, dry chemical.

Fire Fighting Procedures:

Full protective equipment, including self-contained breathing apparatus, is recommended. Water from fog nozzles may be used to prevent pressure build-up.

Fire and Explosion Hazards:

For flammable liquids, vapor/air will ignite when an ignition source is present. In other cases, when heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

SECTION 6. Accidental release measures

Procedures for cleaning up spills or leaks:

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. If material does not contain or is not mixed with an isocyanate activator/hardener: Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly. If the material contains, or is mixed with an isocyanate activator/hardener: Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TMN 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance). Pressure can be generated. Do not seal waste containers for 48 hours to allow CO2 to vent. After 48 hours, material may be sealed and disposed of properly.

Ecological information:

There is no data available on the product. The product should not be allowed to enter drains, water courses or the soil.

SECTION 7. Handling and storage

Precautions to be taken in handling and storing:

Observe label precautions. If combustible (flashpoint between 100 - 200 deg F), keep away from heat, sparks and flame. If flammable (flashpoint less than 100 deg F), also keep away from static discharges and other sources of ignition. If material is extremely flammable (flashpoint less than 20 deg F) or flammable, VAPORS MAY IGNITE EXPLOSIVELY OR CAUSE FLASH FIRE, respectively. Vapors may spread long distances. Prevent buildup of vapors. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 deg F. If product is waterbased, do not freeze.

SECTION 8. Exposure controls / personal protection

Engineering controls and work practices:

Ventilation:

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable exposure limits.

Respiratory protection:

Do not breathe vapors or mists. If this product contains isocyanates or is used with an isocyanate activator/hardener, wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with paint, during application and until all vapors and spray mist are exhausted. If product does not contain or is not mixed with an isocyanate activator/hardener, a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH TC-23C) and particulate filter (NIOSH TC-84A) may be used. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed vapor or spray mist if product contains or is mixed with isocyanate activators/hardeners.

Protective equipment:

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Skin protection:

Neoprene gloves and coveralls are recommended.

Eye protection:

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

SECTION 9. Physical and chemical properties

Evaporation rate	Slower than Ether
Water solubility	NIL
Vapour density	Heavier than air
Approx. Boiling Range (°C)	55 - 472 °C
Approx. Freezing Range (°C)	-134.4 - -107.9 °C
Gallon Weight (lbs/gal)	6.87 - 9.76
Specific Gravity	0.82 - 1.17
Percent Volatile By Volume	0.00 - 91.33
Percent Volatile By Weight	0.00 - 88.89
Percent Solids By Volume	8.67 - 100.00
Percent Solids By Weight	11.11 - 100.00

SECTION 10. Stability and reactivity

Stability:

Stable

Incompatibility (materials to avoid):

None reasonably foreseeable

Hazardous decomposition products:

CO, CO2, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Hazardous Polymerization:
Will not occur.

Sensitivity to Static Discharge:
For flammable materials (flashpoint less than 100 deg F) and combustibles (flashpoint between 100-200 deg F) if heated above the flashpoint, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

Sensitivity to Mechanical Impact:
None known.

SECTION 11. Additional Information

77S™ 1,2,4-trimethyl benzene(2%*), Aromatic hydrocarbon-B, Butyl acetate, Dibutyl tin dilaurate, Ethylbenzene(0.2%* @), Isophorone diisocyanate(0.4% #*), Isophorone diisocyanate homopolymer, Toluene(65%* @)
GAL WT: 7.75 WT PCT SOLIDS: 25.47 VOL PCT SOLIDS: 20.44
SOLVENT DENSITY: 7.26 VOC LE: 5.8 VOC AP: 5.8
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

192S™ 1,2,4-trimethyl benzene(2%*), Aliphatic polyisocyanate resin, Aromatic hydrocarbon-B, Butyl acetate, Ethyl acetate
GAL WT: 8.11 WT PCT SOLIDS: 32.69 VOL PCT SOLIDS: 27.14
SOLVENT DENSITY: 7.49 VOC LE: 5.5 VOC AP: 5.5
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

193S™ 1,6-hexamethylene diisocyanate(0.2%* @), Aliphatic polyisocyanate resin, Butyl acetate, Ethyl acetate, Ethylene glycol monobutyl ether acetate(4%* @)
GAL WT: 9.02 WT PCT SOLIDS: 74.99 VOL PCT SOLIDS: 70.02
SOLVENT DENSITY: 7.53 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 20° F to below 73° F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

194S™ 1,6-hexamethylene diisocyanate(0.2%* @), 2-ethylhexyl acetate, Aliphatic polyisocyanate resin, Butyl acetate, Ethyl acetate
GAL WT: 8.98 WT PCT SOLIDS: 75.00 VOL PCT SOLIDS: 69.76
SOLVENT DENSITY: 7.43 VOC LE: 2.2 VOC AP: 2.2
FLASH POINT: 20° F to below 73° F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

195S™ 1,2,4-trimethyl benzene(0 - 2%*), 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic polyisocyanate resin, Aromatic hydrocarbon-B, Butyl acetate, Ethyl acetate
GAL WT: 8.66 WT PCT SOLIDS: 60.74 VOL PCT SOLIDS: 54.52
SOLVENT DENSITY: 7.48 VOC LE: 3.4 VOC AP: 3.4
FLASH POINT: 20° F to below 73° F H: 2 F: 3 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

196S™ 1,6-hexamethylene diisocyanate(0.1%* @), Acetone, Aliphatic polyisocyanate resin, Ethyl acetate
GAL WT: 8.53 WT PCT SOLIDS: 64.74 VOL PCT SOLIDS: 57.24
SOLVENT DENSITY: 7.03 VOC LE: 1.9 VOC AP: 1.5
FLASH POINT: Below 20° F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

197S™ 1,6-hexamethylene diisocyanate(0.2%* @), Aliphatic polyisocyanate resin, Methyl amyl ketone
GAL WT: 9.45 WT PCT SOLIDS: 95.00 VOL PCT SOLIDS: 93.01
SOLVENT DENSITY: 6.79 VOC LE: 0.5 VOC AP: 0.5
FLASH POINT: 100° F - 141° F H: 2 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

236S™ 2,4,6- tri((dimethylamino)methyl) phenol, Isobutyl alcohol, Isopropyl alcohol, Methyl amyl ketone, N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane, Propylene glycol methyl ether, Salicylic acid, Siloxanes and silane esters, Vm&p naphtha
GAL WT: 7.13 WT PCT SOLIDS: 21.64 VOL PCT SOLIDS: 17.55
SOLVENT DENSITY: 6.78 VOC LE: 5.6 VOC AP: 5.6
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 2 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

255S™ 2,4,6- tri((dimethylamino)methyl) phenol, Isobutyl alcohol, Methyl isobutyl ketone(27%* @), N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane, Salicylic acid, Siloxanes and silane esters
GAL WT: 6.87 WT PCT SOLIDS: 11.11 VOL PCT SOLIDS: 8.67
SOLVENT DENSITY: 6.69 VOC LE: 6.1 VOC AP: 6.1
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 2 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

785S™ 1,6-hexamethylene diisocyanate(0.2%* @), Aliphatic polyisocyanate resin, Methyl ethyl ketone
GAL WT: 9.24 WT PCT SOLIDS: 90.00 VOL PCT SOLIDS: 86.13
SOLVENT DENSITY: 6.74 VOC LE: 0.9 VOC AP: 0.9
FLASH POINT: 20° F to below 73° F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

793S™ 1,2,4-trimethyl benzene(1%*), 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic polyisocyanate resin, Aromatic hydrocarbon-B, Bis(2,2,6,6, tetramethyl-4 piperidyl) sebacate, Butyl acetate, Ethanol, 2-(2-butoxyethoxy)-(6%* @), Ethyl acetate, Substituted benzotriazole, Toluene(4%* @), Trixylenyl phosphate
GAL WT: 9.14 WT PCT SOLIDS: 78.77 VOL PCT SOLIDS: 74.12
SOLVENT DENSITY: 7.49 VOC LE: 1.9 VOC AP: 1.9
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

795S™ 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic polyisocyanate resin, Butyl acetate, Ethyl acetate, Ethylene glycol monobutyl ether acetate(6%* @)
GAL WT: 8.82 WT PCT SOLIDS: 66.78 VOL PCT SOLIDS: 61.06
SOLVENT DENSITY: 7.53 VOC LE: 2.9 VOC AP: 2.9
FLASH POINT: 20° F to below 73° F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

2000S-B™ 1,2,4-trimethyl benzene(1%*), 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic polyisocyanate resin, Aromatic hydrocarbon-B, Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate, Butyl acetate, Substituted benzotriazole, Toluene(7%* @), Trixylenyl phosphate
GAL WT: 9.25 WT PCT SOLIDS: 84.70 VOL PCT SOLIDS: 80.62
SOLVENT DENSITY: 7.27 VOC LE: 1.4 VOC AP: 1.4
FLASH POINT: 20° F to below 73° F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

2202S™ 1,6-hexamethylene diisocyanate(0.2%* @), Aliphatic polyisocyanate resin
GAL WT: 9.76 WT PCT SOLIDS: 100.00 VOL PCT SOLIDS: 100.00
SOLVENT DENSITY: 0.00 VOC LE: 0.0 VOC AP: 0.0
FLASH POINT: Above 200° F H: 3 F: 1 R: 1 OSHA STORAGE: IIIB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

4505S™ 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic polyisocyanate resin, Butyl acetate, Hexyl acetate isomers, Isophorone diisocyanate homopolymer
GAL WT: 8.94 WT PCT SOLIDS: 73.54 VOL PCT SOLIDS: 67.58
SOLVENT DENSITY: 7.31 VOC LE: 2.4 VOC AP: 2.4
FLASH POINT: 100° F - 141° F H: 3 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

4507S™ 1,6-hexamethylene diisocyanate(0.1%* @), Aliphatic

polyisocyanate resin, Butyl acetate, Hexyl acetate isomers, Isophorone diisocyanate homopolymer, Methyl amyl ketone
GAL WT: 8.84 WT PCT SOLIDS: 73.36 VOL PCT SOLIDS: 66.94
SOLVENT DENSITY: 7.07 VOC LE: 2.4 VOC AP: 2.4
FLASH POINT: 100°F - 141°F H: 3 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

7005S™ 1,2,4-trimethyl benzene(1%*), 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Aromatic hydrocarbon-B, Butyl acetate, Diisobutyl ketone, Ethyl acetate
GAL WT: 8.73 WT PCT SOLIDS: 65.29 VOL PCT SOLIDS: 58.38
SOLVENT DENSITY: 7.27 VOC LE: 3.0 VOC AP: 3.0
FLASH POINT: 20°F to below 73°F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

7006S™ 1,6-hexamethylene diisocyanate(0.1%*), 4,6-dimethyl-2-heptanone, Aliphatic polyisocyanate resin, Diisobutyl ketone, Propylene glycol monomethyl ether acetate
GAL WT: 8.91 WT PCT SOLIDS: 73.86 VOL PCT SOLIDS: 68.17
SOLVENT DENSITY: 7.29 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 100°F - 141°F H: 2 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

7765S™ 2-methyl butyl acetate, Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%), Primary amyl acetate, Toluene(13%*)
GAL WT: 8.29 WT PCT SOLIDS: 47.03 VOL PCT SOLIDS: 40.06
SOLVENT DENSITY: 7.31 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

7775S™ Aliphatic polyisocyanate resin, Butyl acetate, Ethyl 3-ethoxy propionate, Ethylbenzene(1.3%*), Isophorone diisocyanate homopolymer, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%), Primary amyl acetate, Toluene(7%*), Xylene(5%*)
GAL WT: 8.32 WT PCT SOLIDS: 47.01 VOL PCT SOLIDS: 40.21
SOLVENT DENSITY: 7.36 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

7785S™ 2-ethylhexyl acetate, Aliphatic polyisocyanate resin, Butyl acetate, Ethyl 3-ethoxy propionate, Ethylbenzene(1.3%*), Isophorone diisocyanate homopolymer, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%), Xylene(5%*)
GAL WT: 8.34 WT PCT SOLIDS: 46.97 VOL PCT SOLIDS: 40.26
SOLVENT DENSITY: 7.39 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 100°F - 141°F H: 3 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

7795S™ 2-ethylhexyl acetate, Aliphatic polyisocyanate resin, Butyl acetate, Ethyl 3-ethoxy propionate, Isophorone diisocyanate homopolymer, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%)
GAL WT: 8.33 WT PCT SOLIDS: 46.97 VOL PCT SOLIDS: 40.18
SOLVENT DENSITY: 7.37 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 100°F - 141°F H: 3 F: 2 R: 1 OSHA STORAGE: II
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

8105S™ 4,6-dimethyl-2-heptanone, Aliphatic polyisocyanate resin, Aromatic hydrocarbon-A, Aromatic hydrocarbon-B, Butyl acetate, Diisobutyl ketone, Ethylbenzene(2.3%*), Naphthalene(0.8%*), Xylene(9%*)
GAL WT: 8.12 WT PCT SOLIDS: 41.96 VOL PCT SOLIDS: 34.91
SOLVENT DENSITY: 7.23 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: YES

8195S™ Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate, Butyl acetate, Ethanol, 2-(2-butoxyethoxy)-(4%*), Ethyl 3-ethoxy propionate,

Ethylbenzene(0.6 - 1.5%*), Ethylene glycol monobutyl ether acetate(16%*), Polyester resin, Substituted benzotriazole, Vm&p naphtha, Xylene(4 - 5%*)
GAL WT: 7.94 WT PCT SOLIDS: 35.49 VOL PCT SOLIDS: 30.94
SOLVENT DENSITY: 7.39 VOC LE: 5.1 VOC AP: 5.1
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

12301S™ 1,6-hexamethylene diisocyanate(0.2%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%)
GAL WT: 8.30 WT PCT SOLIDS: 57.71 VOL PCT SOLIDS: 49.93
SOLVENT DENSITY: 6.97 VOC LE: 3.5 VOC AP: 3.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

12303S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.52 WT PCT SOLIDS: 65.00 VOL PCT SOLIDS: 57.13
SOLVENT DENSITY: 6.92 VOC LE: 3.0 VOC AP: 3.0
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

12305S™ 1,6-hexamethylene diisocyanate(0.1%*), 4,6-dimethyl-2-heptanone, Aliphatic polyisocyanate resin, Butyl acetate, Diisobutyl ketone, Methyl amyl ketone
GAL WT: 8.51 WT PCT SOLIDS: 65.00 VOL PCT SOLIDS: 56.65
SOLVENT DENSITY: 6.88 VOC LE: 3.0 VOC AP: 3.0
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

G2-4507S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.85 WT PCT SOLIDS: 73.50 VOL PCT SOLIDS: 67.07
SOLVENT DENSITY: 7.06 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

G2-4508S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.85 WT PCT SOLIDS: 73.48 VOL PCT SOLIDS: 67.05
SOLVENT DENSITY: 7.06 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

G2-4509S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.85 WT PCT SOLIDS: 73.36 VOL PCT SOLIDS: 66.91
SOLVENT DENSITY: 7.06 VOC LE: 2.4 VOC AP: 2.4
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

HC-4575S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.85 WT PCT SOLIDS: 73.50 VOL PCT SOLIDS: 67.07
SOLVENT DENSITY: 7.06 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALY REACTIVE: NO

HC-4585S™ 1,6-hexamethylene diisocyanate(0.1%*), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate
GAL WT: 8.85 WT PCT SOLIDS: 73.48 VOL PCT SOLIDS: 67.05

SOLVENT DENSITY: 7.06 VOC LE: 2.3 VOC AP: 2.3
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

HC-4595S™ 1,6-hexamethylene diisocyanate(0.1%*@), Aliphatic polyisocyanate resin, Butyl acetate, Isophorone diisocyanate homopolymer, Methyl amyl ketone, N-pentyl propionate

GAL WT: 8.85 WT PCT SOLIDS: 73.36 VOL PCT SOLIDS: 66.91
SOLVENT DENSITY: 7.06 VOC LE: 2.4 VOC AP: 2.4
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

LH7775™ Aliphatic polyisocyanate resin, Butyl acetate, Ethyl 3-ethoxy propionate, Isophorone diisocyanate homopolymer, Methyl ethyl ketone, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%), Primary amyl acetate

GAL WT: 8.24 WT PCT SOLIDS: 47.00 VOL PCT SOLIDS: 40.24
SOLVENT DENSITY: 7.31 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

LH7785™ 2-ethylhexyl acetate, Aliphatic polyisocyanate resin, Butyl acetate, Ethyl 3-ethoxy propionate, Isophorone diisocyanate homopolymer, N-pentyl propionate, P-toluenesulfonyl isocyanate(0.2%)

GAL WT: 8.32 WT PCT SOLIDS: 47.00 VOL PCT SOLIDS: 40.60
SOLVENT DENSITY: 7.40 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 73°F to below 100°F H: 2 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

V-12305S™ 1,6-hexamethylene diisocyanate(0.1%*@), 4-chlorobenzotrifluoride, Aliphatic polyisocyanate resin, Methyl acetate, N-pentyl propionate

GAL WT: 9.26 WT PCT SOLIDS: 72.00 VOL PCT SOLIDS: 69.64
SOLVENT DENSITY: 8.53 VOC LE: 0.4 VOC AP: 0.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

V-12307S™ 1,6-hexamethylene diisocyanate(0.2%*@), 4-chlorobenzotrifluoride, Aliphatic polyisocyanate resin, Ethyl 3-ethoxy propionate, Methyl acetate

GAL WT: 9.60 WT PCT SOLIDS: 69.89 VOL PCT SOLIDS: 70.20
SOLVENT DENSITY: 9.69 VOC LE: 0.4 VOC AP: 0.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

V-192S™ Aliphatic polyisocyanate resin, Heptane, Methyl amyl ketone, Methyl ethyl ketone, Toluene(26%*@)

GAL WT: 7.69 WT PCT SOLIDS: 38.39 VOL PCT SOLIDS: 30.25
SOLVENT DENSITY: 6.82 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 3 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

Footnotes:

TSCA: in compliance = In compliance with TSCA Inventory requirements for commercial purposes.

ACGIH = American Conference of Governmental Industrial Hygienists.

IARC = International Agency for Research on Cancer.

NTP = National Toxicology Program.

OSHA = Occupational Safety and Health Administration.

PNOR = Particles not otherwise regulated.

PNOC = Particles not otherwise classified.

STEL = Short term exposure limit.

TWA = Time-weighted average.

™ = Is a Trademark of E.I. DuPont de Nemours Co.

* = Section 313 Supplier Notification: These chemicals are subject to the reporting requirements of Section 313 of the Emergency planning and Right-to-Know act of 1986 and of 40 CFR 372.

@ = Listed as a Clean Air Act Hazardous Air Pollutant.

= EPCRA Section 302 - Extremely hazardous substances.

Notice:

The information on this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Product Manager: Refinish Sales

Prepared by: Y. B. Yarbrough