

SECTION 1. Identification of the substance/preparation and of the company/undertaking

Manufacturer: E.I. du Pont de Nemours & Co.
 DuPont Performance Coatings
 Wilmington, DE, 19898

Telephone: Product information: (800) 441-7515
 Medical emergency: (800) 441-3637
 Transportation emergency: (800) 424-9300
 (CHEMTREC)

Product: **Centari® Acrylic Enamel Tints and Miscellaneous
 Factory Packaged Colors**

DOT Shipping Name: See DOT Addendum.

Hazardous Materials Information: See Section 10.

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
Antimony	7440-36-0	None	Respirable Dust A 0.5 mg/m3 Sb O 0.5 mg/m3 Sb
Antimony pentoxide	1314-60-9	None	A 0.5 mg/m3 Sb O 0.5 mg/m3 Sb
Antimony trioxide	1309-64-4	None	A 0.5 mg/m3 Sb O 0.5 mg/m3 Sb D 0.2 mg/m3 Sb D 0.1 mg/m3 12 hr TWA Sb

Copyright 2007 E. I. duPont de Nemours and Company. All rights reserved. Copies may be made only for those using DuPont products.

SECTION 2. Composition/information on ingredients

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
1,2,4-trimethyl benzene	95-63-6	7.0@44.4°C	A 25.0 ppm O 25.0 ppm
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	25265-77-4	0.0	A None O None
4,6-dimethyl-2-heptanone	19549-80-5	None	A None O None
Acetone	67-64-1	247.0@68.0°F	A 750.0 ppm 15 min STEL A 500.0 ppm O 1000.0 ppm D 500.0 ppm 8 & 12 hour TWA
Acrylic polymer-A	79084-85-8	None	A None O None
Acrylic polymer-B	96591-17-2	None	A None O None
Aliphatic polyisocyanate resin	28182-81-2	None	S 1.0 mg/m3 15 min STEL S 0.5 mg/m3 A None O None
Alkyd resin	67922-67-2	None	A None O None
Aluminum	7429-90-5	None	A 10.0 mg/m3 particulate A 5.0 mg/m3 Dust O 15.0 mg/m3 Total Dust O 5.0 mg/m3
Aromatic hydrocarbon-A	64742-94-5	10.0	D 100.0 ppm A None O None
Aromatic hydrocarbon-B	64742-95-6	10.0@25.0°C	D 50.0 ppm A None O None
Azo yellow pigment	31837-42-0	None	A 10.0 mg/m3 O 5.0 mg/m3 Respirable Dust O 15.0 mg/m3
Barium sulfate	7727-43-7	None	A 10.0 mg/m3 Total Dust A 5.0 mg/m3 Respirable Dust O 15.0 mg/m3 Total Dust O 5.0 mg/m3 8 & 12 hour TWA Respirable Dust
Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l sebacate	41556-26-7	None	A None O None
Butyl acetate	123-86-4	10.0	A 200.0 ppm 15 min STEL A 150.0 ppm O 150.0 ppm
C.i. pigment blue 15 (monochlor)	12239-87-1	None	A 10.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust Total Dust O 15.0 mg/m3

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS	INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
C.i. pigment yellow 154	68134-22-5	None	Respirable Dust A None O None	Isoindolinone pigment-A	36888-99-0	None	O 10.0 mg/m3 A None O None
Carbon black	1333-86-4	None	A 3.5 mg/m3 O 3.5 mg/m3 D 0.5 mg/m3 8 & 12 hour TWA	Isoindolinone pigment-B	106276-80-6	None	A None O None
Castor oil, dehydrated	64147-40-6	None	A None O None	Isoindolinone yellow pigment	106276-79-3	None	A None O None
Chromium(iii)	7440-47-3	None	A 0.5 mg/m3 Cr O 0.5 mg/m3 Cr	Lead chromate molybdate	12656-85-8	None	A 50.0 ug/m3 Pb A 10.0 mg/m3 inhalable dust Mo A 3.0 mg/m3 respirable particulate Mo A 12.0 ug/m3 Cr(VI) O 50.0 ug/m3 Pb O 5.0 ug/m3 Cr(VI)
Cobalt naphthenate	61789-51-3	0.8	A 50.0 ug/m3 Co O 50.0 ug/m3 Co	Lead chromate oxide	18454-12-1	None	A 50.0 ug/m3 Pb A 12.0 ug/m3 Cr(VI) O 50.0 ug/m3 Pb O 5.0 ug/m3 Cr(VI)
Diisobutyl ketone	108-83-8	1.8	A 25.0 ppm O 50.0 ppm	Lead chromates	7758-97-6	None	A 50.0 ug/m3 Pb A 12.0 ug/m3 Cr(VI) O 50.0 ug/m3 Pb O 5.0 ug/m3 Cr(VI)
Dioxazine carbozole pigment	4378-61-4	None	A 10.0 mg/m3 O 5.0 mg/m3 Respirable Dust O 15.0 mg/m3	Manganese alkanoate	NotAvail	None	A 0.2 mg/m3 Mn O 0.5 mg/m3 CEIL Mn
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	0.0	D 5.0 ppm A None O None	Medium mineral spirits	64742-88-7	0.3@68.0°F	D 50.0 ppm 8 & 12 hour TWA A None O None
Ethyl 3-ethoxy propionate	763-69-9	1.1@25.0°C	A None O None	Methyl amyl ketone	110-43-0	3.4	A 50.0 ppm O 100.0 ppm
Ethyl acetate	141-78-6	93.2@25.0°C	A 400.0 ppm O 400.0 ppm	Methyl ethyl ketone	78-93-3	71.2	A 300.0 ppm 15 min STEL
Ethylbenzene	100-41-4	7.0	A 125.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 25.0 ppm 8 & 12 hour TWA				
Ethylene glycol monobutyl ether acetate	112-07-2	0.3	A 20.0 ppm D 20.0 ppm 8 & 12 hour TWA O None				
Ferrate(4-), hexacyano-, iron (+3) (3:4)	14038-43-8	None	A None O None				
Iron oxide-A	1309-37-1	None	A 5.0 mg/m3 Respirable Dust O 10.0 mg/m3 D 3.0 mg/m3				
Iron oxide-B	51274-00-1	None	A 5.0 mg/m3				

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS	INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
			A 200.0 ppm O 200.0 ppm D 300.0 ppm 15 min TWA D 200.0 ppm 8 & 12 hour TWA		1328-53-6	None	A 3.0 mg/m3 TWA Respirable Dust A 10.0 mg/m3 TWA inhalable dust O 15.0 mg/m3 TWA Total Dust O 5.0 mg/m3 TWA Respirable Dust
Monoazo pigment	12236-62-3	None	A 10.0 mg/m3 inhalable dust particulate O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust	Phthalocyanine green pigment	68512-13-0	None	A None O None
Naphthalene	91-20-3	None	A 15.0 ppm CEIL Skin A 10.0 ppm Skin O 10.0 ppm D 0.1 ppm 8 & 12 hour TWA	Pigment red 202	3089-17-6	None	A 3.0 mg/m3 Respirable Dust A 10.0 mg/m3 inhalable dust PNOR O 5.0 mg/m3 Respirable Dust PNOR O 15.0 mg/m3
Nickel oxide	1313-99-1	None	A 0.2 mg/m3 inhalable dust Ni O 1.0 mg/m3 Ni D 20.0 ug/m3 8 & 12 hour TWA Ni	Polyester resin-A	NotAvail	None	A None O None
				Polyester resin-B	114615-84-8	None	A None O None
Oxo-octyl acetate	108419-32-5	0.7@25.0°C	S 10.0 mg/m3 Aerosol S 50.0 ppm Vapor A None O None	Polyethylene glycol diethyl hexoate	18268-70-7	0.1	A None O None
				Propylene carbonate	108-32-7	0.0	A None O None
Perylene pigment	5521-31-3	None	A 10.0 mg/m3 O None	Propylene glycol monomethyl ether acetate	108-65-6	3.8	D 10.0 ppm 8 & 12 hour TWA A None O None
Phthalocyanine blue	29719-96-8	None	A 10.0 mg/m3 O 5.0 mg/m3 Respirable Dust O 15.0 mg/m3	Quinacridone magenta	980-26-7	None	A None O None
Phthalocyanine blue pigment	147-14-8	None	A 10.0 mg/m3 inhalable dust PNOC A 3.0 mg/m3 respirable particulate PNOC O 15.0 mg/m3 Total Dust PNOR O 5.0 mg/m3 TWA Respirable Dust PNOR	Quinacridone pigment	1047-16-1	None	A 10.0 mg/m3 inhalable dust A 3.0 mg/m3 O 15.0 mg/m3 Total Dust PNOR O 5.0 mg/m3 Respirable Dust D 10.0 mg/m3 Total Dust
				Red iron oxide light	1332-37-2	None	A 10.0 mg/m3 PNOR A 3.0 mg/m3 Respirable Dust A 5.0 mg/m3 Fe

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
Substituted benzotriazole	25973-55-1	None	O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust A None O None
Thio fast red-thio indigo pigment	14295-43-3	None	A 10.0 mg/m3 O None
Titanium dioxide	13463-67-7	None	A 10.0 mg/m3 O 15.0 mg/m3 Total Dust D 10.0 mg/m3 Total Dust D 5.0 mg/m3 Respirable Dust
Titanium dioxide (rutile)	1317-80-2	None	A 10.0 mg/m3 TWA Total Dust O 10.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust D 10.0 mg/m3 Total Dust D 5.0 mg/m3 Respirable Dust
Toluene	108-88-3	22.0	A 20.0 ppm O 300.0 ppm CEIL O 500.0 ppm 10 min TWA O 200.0 ppm D 50.0 ppm 8 & 12 hour TWA
Vm&p naphtha	8032-32-4	17.9@68.0°F	A 300.0 ppm D 100.0 ppm O None
Xylene	1330-20-7	8.0@25.0°C	A 150.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 150.0 ppm 15 min STEL D 100.0 ppm 8 & 12 hour TWA
Yellow iron oxide	51274-00-1	None	A 10.0 mg/m3 O 15.0 mg/m3
Zirconium octoate	22464-99-9	1.0@25.0°C	A 10.0 mg/m3 15 min STEL A 5.0 mg/m3 Zr O 10.0 mg/m3 15 min STEL

*A=ACGIH, O=OSHA, D=DuPont, S=Suppliers. Limits are 8 hour TWA unless otherwise specified. Vapor pressure @ 20° C unless otherwise noted.

SECTION 3. Hazards identification

Potential Health Effects:

Inhalation:

May cause nose and throat irritation. May cause nervous system depression, characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product contains or is mixed with an isocyanate activator/hardener, the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion:

May result in gastrointestinal distress.

Skin or eye contact:

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Other Potential Health Effects in addition to those listed above:

Acetone

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

Aliphatic polyisocyanate resin

Overexposure may cause asthma-like reactions with shortness of breath, wheezing, cough, which may be permanent; or permanent lung sensitization. This effect may be delayed for several hours after exposure. The following medical conditions may be aggravated by exposure: asthma, skin disorders, respiratory disorders. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin. Skin or eye contact may cause any of the following: irritation.

Antimony trioxide

Is an IARC, NTP or OSHA carcinogen. Cancer hazard based on tests with laboratory animals. Overexposure may create cancer risk This substance may cause effects on any of the following organs/systems: lungs. Tests in laboratory animals have shown potential for developmental toxicity. The significance to man is unknown.
WARNING: This chemical is known to the State of California to cause cancer.

Aromatic hydrocarbon-A

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Aromatic hydrocarbon-B

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate

Repeated exposure may cause allergic skin rash, itching, swelling.

Butyl acetate

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

C.i. pigment yellow 154

Inhalation may cause any of the following: respiratory tract irritation. Skin or eye contact may cause any of the following: irritation.

Carbon black

Is an IARC, NTP or OSHA carcinogen. Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. The following medical conditions may be aggravated by exposure: asthma, respiratory disease.

WARNING: This chemical is known to the State of California to cause cancer.

Cobalt naphthenate

Contact may cause skin irritation with discomfort or rash. Some cobalt compounds may be possible human carcinogens.

Diisobutyl ketone

The following medical conditions may be aggravated by exposure: asthma, blood, dermatitis. Contact may cause skin irritation with discomfort or rash. Repeated exposure may cause allergic skin rash, itching, swelling. This substance may cause damage to any of the following organs/systems: eyes, kidneys, liver. Extremely high oral and inhalation doses in laboratory animals have shown weight changes in various organs such as the liver, kidney, brain, heart and adrenal gland. In addition liver and kidney injury were observed at the extremely high inhalation level. In another inhalation study there was a slight depression in the white blood cell count. Liquid or vapor causes irritation, experienced as stinging, excess blinking and tear production, with excess redness and swelling of the conjunctiva.

Ethanol, 2-(2-butoxyethoxy)-

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, kidneys, liver, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver. Recurrent overexposure may result in liver and kidney injury. High doses in laboratory animals have shown non specific effects such as irritation, weight loss, moderate blood changes. Eye contact may cause any of the following: severe irritation, burns, corneal injury.

Ethyl acetate

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

Ethylbenzene

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects.

WARNING: This chemical is known to the State of California to cause cancer.

Ethylene glycol monobutyl ether acetate

May destroy red blood cells. May cause abnormal kidney function. May cause temporary upper respiratory and/or lung irritation with cough, difficult breathing, or shortness of breath. The following medical conditions may be aggravated by exposure: central nervous system, gastrointestinal system, kidneys, liver, dermatitis. Can be absorbed through the skin in harmful amounts. Overexposure may cause damage to any of the following organs/systems: blood, kidneys, liver. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

Lead chromate molybdate

Is an IARC, NTP or OSHA carcinogen. Over exposure to lead may cause adverse effects to the blood forming, nervous, urinary, reproductive systems including embryotoxic effects. Symptoms may include loss of appetite, anemia, disturbance of sleep and fatigue. See OSHA lead standard 29CFR1910.1025. For exposures longer than 8 hours the OSHA exposure limit is reduced by this formula: $\text{limit(in ug/m}^3\text{)} = 400/\text{hours}$ worked in the day. Health studies have shown that chromate pigment manufacturing may be associated with an increase risk of lung cancer. Repeated or prolonged skin contact may cause any of the following: dermatitis, allergic skin rash. The following medical conditions may be aggravated by overexposure: asthma. Repeated or prolonged skin or eye contact may cause any of the following: irritation. Repeated or prolonged inhalation may cause any of the following: respiratory tract irritation, sensitization, asthma-like reactions, e.g. wheezing, chest tightness. WARNING: This chemical is known to the State of California to cause cancer and birth defects or other reproductive harm

Lead chromate oxide

Is an IARC, NTP or OSHA carcinogen. Over exposure to lead may cause adverse effects to the blood forming, nervous, urinary, reproductive systems including embryotoxic effects. Symptoms may include loss of appetite, anemia, disturbance of sleep and fatigue. See OSHA lead standard 29CFR1910.1025. For exposures longer than 8 hours the OSHA exposure limit is reduced by this formula: $\text{limit(in ug/m}^3\text{)} = 400/\text{hours}$ worked in the day. Health studies have shown that chromate pigment manufacturing may be associated with an increase risk of lung cancer. Repeated or prolonged skin contact may cause any of the following: dermatitis, allergic skin rash. The following medical conditions may be aggravated by overexposure: asthma. Repeated or prolonged skin or eye contact may cause any of the following: irritation. Repeated or prolonged inhalation may cause any of the following: respiratory tract irritation, sensitization, asthma-like reactions, e.g. wheezing, chest tightness. WARNING: This chemical is known to the State of California to cause cancer and birth defects or other reproductive harm

Lead chromates

Is an IARC, NTP or OSHA carcinogen. Over exposure to lead may cause adverse effects to the blood forming, nervous, urinary, reproductive systems including embryotoxic effects. Symptoms may include loss of appetite, anemia, disturbance of sleep and fatigue. See OSHA lead standard 29CFR1910.1025. For exposures longer than 8 hours the OSHA exposure limit is reduced by this formula: $\text{limit(in ug/m}^3\text{)} = 400/\text{hours}$ worked in the day. Health studies have shown that chromate pigment manufacturing may be associated with an increase risk of lung cancer. Repeated or prolonged skin contact may cause any of the following: dermatitis, allergic skin rash. The following medical conditions may be aggravated by overexposure: asthma. Repeated or prolonged skin or eye contact may cause any of the following: irritation. Repeated or prolonged inhalation may cause any of the following: respiratory tract irritation, sensitization, asthma-like reactions, e.g. wheezing, chest tightness. WARNING: This chemical is known to the State of California to cause cancer and birth defects or other reproductive harm

Manganese alkanoate

Contact may cause skin irritation with discomfort or rash.

Medium mineral spirits

Increased susceptibility to the effects of this material may be observed in

people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

Methyl ethyl ketone

Material is irritating to mucous membranes and upper respiratory tract. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, respiratory system, skin. Prolonged or repeated overexposure may cause any of the following: conjunctivitis, dermatitis. High concentrations have caused embryotoxic effects in laboratory animals. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

Naphthalene

Is an IARC, NTP or OSHA carcinogen. Tests in some laboratory animals demonstrate carcinogenic activity. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: kidneys, liver. Recurrent overexposure may result in liver and kidney injury.

WARNING: This chemical is known to the State of California to cause cancer.

Nickel oxide

Is an IARC, NTP or OSHA carcinogen. Skin contact may cause any of the following: skin sensitization, skin irritation. Overexposure of this substance may cause effects on any of the following organs/systems: lungs.

WARNING: This chemical is known to the State of California to cause cancer.

Oxo-octyl acetate

May cause any of the following central nervous system effects: dizziness, headache.

Propylene glycol monomethyl ether acetate

Recurrent overexposure may result in liver and kidney injury.

Red iron oxide light

Long-term respiratory exposure of iron oxide may result in deposition of particles in the lung (benign siderosis).

Substituted benzotriazole

The following medical conditions may be aggravated by exposure: jaundice, liver disease. Repeated or prolonged ingestion may cause any of the following: changes in the blood, liver effects.

Titanium dioxide

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

Titanium dioxide (rutile)

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable

titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

Toluene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown.

WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

Vm&p naphtha

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs, respiratory system, skin. This substance may cause damage to any of the following organs/systems: central nervous system, kidneys, liver, lungs, skin and eyes. Material may be harmful or fatal if swallowed.

Xylene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

SECTION 4. First aid measures

First Aid Procedures:

Inhalation:

If affected by inhalation of vapor or spray mist, move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulty persists, or occurs later, consult a physician.

Ingestion:

In the unlikely event of ingestion, DO NOT INDUCE VOMITING. Call a physician immediately and have names of ingredients available.

Skin or eye contact:

In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, contact a physician.

SECTION 5. Fire-fighting measures

Flash Point (Closed Cup): See Section 11 for exact values.

Flammable Limits: LFL 0.5 % UFL 24.6 %

Extinguishing Media:

Universal aqueous film-forming foam, carbon dioxide, dry chemical.

Fire Fighting Procedures:

Full protective equipment, including self-contained breathing apparatus, is recommended. Water from fog nozzles may be used to prevent pressure build-up.

Fire and Explosion Hazards:

For flammable liquids, vapor/air will ignite when an ignition source is present. In other cases, when heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

SECTION 6. Accidental release measures

Procedures for cleaning up spills or leaks:

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. If material does not contain or is not mixed with an isocyanate activator/hardener: Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly. If the material contains, or is mixed with an isocyanate activator/hardener: Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TMN 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance). Pressure can be generated. Do not seal waste containers for 48 hours to allow CO₂ to vent. After 48 hours, material may be sealed and disposed of properly.

Ecological information:

There is no data available on the product. The product should not be allowed to enter drains, water courses or the soil.

SECTION 7. Handling and storage

Precautions to be taken in handling and storing:

Observe label precautions. If combustible (flashpoint between 100 - 200 deg F), keep away from heat, sparks and flame. If flammable (flashpoint less than 100 deg F), also keep away from static discharges and other sources of ignition. If material is extremely flammable (flashpoint less than 20 deg F) or flammable, VAPORS MAY IGNITE EXPLOSIVELY OR CAUSE FLASH FIRE, respectively. Vapors may spread long distances. Prevent buildup of vapors. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 deg F. If product is waterbased, do not freeze.

Other precautions:

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

SECTION 8. Exposure controls / personal protection

Engineering controls and work practices:

Ventilation:

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable exposure limits.

Respiratory protection:

Do not breathe vapors or mists. If this product contains isocyanates or is used with an isocyanate activator/hardener, wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with paint, during application and until all vapors and spray mist are exhausted. If product does not contain or is not mixed with an isocyanate activator/hardener, a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH TC-23C) and particulate filter (NIOSH TC-84A) may be used. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed vapor or spray mist if product contains or is mixed with isocyanate activators/hardeners.

Protective equipment:

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Skin protection:

Neoprene gloves and coveralls are recommended.

Eye protection:

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

SECTION 9. Physical and chemical properties

Evaporation rate	Slower than Ether
Water solubility	NIL
Vapour density	Heavier than air
Approx. Boiling Range (°C)	77 - 260.5 °C
Approx. Freezing Range (°C)	-93.3 - -60 °C
Gallon Weight (lbs/gal)	6.88 - 9.63
Specific Gravity	0.82 - 1.15
Percent Volatile By Volume	56.71 - 95.95
Percent Volatile By Weight	45.24 - 94.20
Percent Solids By Volume	4.05 - 43.29
Percent Solids By Weight	5.80 - 54.76

SECTION 10. Stability and reactivity

Stability:

Stable

Incompatibility (materials to avoid):

None reasonably foreseeable

Hazardous decomposition products:

CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Hazardous Polymerization:

Will not occur.

Sensitivity to Static Discharge:

For flammable materials (flashpoint less than 100 deg F) and combustibles (flashpoint between 100-200 deg F) if heated above the flashpoint, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

Sensitivity to Mechanical Impact:

None known.

SECTION 11. Additional Information

700A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(4.2%*), Methyl ethyl ketone, Naphthalene(0.1%*), Titanium dioxide(14.9%), Toluene(11%*), Vm&p naphtha, Xylene(17%*)
GAL WT: 8.99 WT PCT SOLIDS: 52.20 VOL PCT SOLIDS: 38.85
SOLVENT DENSITY: 7.01 VOC LE: 4.3 VOC AP: 4.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

701A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(4.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Titanium dioxide(3.0%), Toluene(15%*), Vm&p naphtha, Xylene(19%*)
GAL WT: 8.31 WT PCT SOLIDS: 51.48 VOL PCT SOLIDS: 43.29
SOLVENT DENSITY: 7.10 VOC LE: 4.0 VOC AP: 4.0
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

705A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Carbon black(0.5%), Ethylbenzene(5.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Propylene glycol monomethyl ether acetate, Toluene(12%*), Vm&p naphtha, Xylene(23%*)
GAL WT: 7.89 WT PCT SOLIDS: 40.63 VOL PCT SOLIDS: 33.78
SOLVENT DENSITY: 7.05 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

706A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(5.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(13%*), Vm&p naphtha, Xylene(23%*)
GAL WT: 7.87 WT PCT SOLIDS: 42.30 VOL PCT SOLIDS: 35.27
SOLVENT DENSITY: 7.00 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

710A™ Acrylic polymer-B, Alkyd resin, Aluminum(2%), Aromatic hydrocarbon-A, Ethylbenzene(5.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(13%*), Vm&p naphtha, Xylene(23%*)
GAL WT: 7.94 WT PCT SOLIDS: 42.51 VOL PCT SOLIDS: 35.00
SOLVENT DENSITY: 7.00 VOC LE: 4.6 VOC AP: 4.6
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

711A™ Acrylic polymer-B, Alkyd resin, Aluminum(1%), Aromatic hydrocarbon-A, Ethylbenzene(6.0%*), Methyl ethyl ketone, Naphthalene(0.3%*), Toluene(12%*), Vm&p naphtha, Xylene(24%*)
GAL WT: 7.92 WT PCT SOLIDS: 40.78 VOL PCT SOLIDS: 33.55
SOLVENT DENSITY: 7.05 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

713A™ Acrylic polymer-B, Alkyd resin, Aluminum(2%), Aromatic hydrocarbon-A, Ethylbenzene(5.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(13%*), Vm&p naphtha, Xylene(22%*)
GAL WT: 8.05 WT PCT SOLIDS: 44.86 VOL PCT SOLIDS: 37.07
SOLVENT DENSITY: 7.04 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

715A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(6.2%*), Manganese alkanoate(7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(11%*), Vm&p naphtha, Xylene(25%*)
GAL WT: 8.13 WT PCT SOLIDS: 44.73 VOL PCT SOLIDS: 36.51
SOLVENT DENSITY: 7.07 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

716A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(5.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Thio fast red-thio indigo pigment, Toluene(13%*), Vm&p naphtha, Xylene(21%*)
GAL WT: 7.95 WT PCT SOLIDS: 43.35 VOL PCT SOLIDS: 35.82
SOLVENT DENSITY: 7.00 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

717A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(5.5%*), Methyl ethyl ketone, Naphthalene(0.1%*), Red iron oxide light, Toluene(10%*), Vm&p naphtha, Xylene(21%*)
GAL WT: 8.29 WT PCT SOLIDS: 47.26 VOL PCT SOLIDS: 37.72
SOLVENT DENSITY: 7.02 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

718A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(6.0%*), Methyl ethyl ketone, Naphthalene(0.1%*), Quinacridone pigment, Toluene(8%*), Vm&p naphtha, Xylene(22%*)
GAL WT: 7.90 WT PCT SOLIDS: 42.85 VOL PCT SOLIDS: 35.53
SOLVENT DENSITY: 7.00 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

720A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(6.5%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine blue pigment, Toluene(11%*), Vm&p naphtha, Xylene(26%*)
GAL WT: 7.91 WT PCT SOLIDS: 40.81 VOL PCT SOLIDS: 33.62
SOLVENT DENSITY: 7.05 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

721A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(5.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine blue pigment, Toluene(22%*), Vm&p naphtha, Xylene(21%*)
GAL WT: 7.99 WT PCT SOLIDS: 41.29 VOL PCT SOLIDS: 34.28
SOLVENT DENSITY: 7.13 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

722A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(7.7%*), Isoindolinone yellow pigment, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(4%*), Vm&p naphtha, Xylene(30%*)
GAL WT: 8.09 WT PCT SOLIDS: 41.53 VOL PCT SOLIDS: 33.42
SOLVENT DENSITY: 7.10 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

723A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(5.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(10%*), Vm&p naphtha, Xylene(23%*)
GAL WT: 7.85 WT PCT SOLIDS: 41.18 VOL PCT SOLIDS: 34.07
SOLVENT DENSITY: 7.00 VOC LE: 4.6 VOC AP: 4.6
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

724A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(6.9%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine blue, Toluene(9%*), Vm&p naphtha, Xylene(27%*)
GAL WT: 8.03 WT PCT SOLIDS: 42.25 VOL PCT SOLIDS: 35.23
SOLVENT DENSITY: 7.16 VOC LE: 4.6 VOC AP: 4.6
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB

TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

725A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(6.5%*), Ferrate(4-), hexacyano-, iron (+3) (3:4)(7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(10%*), Vm&p naphtha, Xylene(26%*)

GAL WT: 8.02 WT PCT SOLIDS: 40.96 VOL PCT SOLIDS: 32.60
SOLVENT DENSITY: 7.02 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

726A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(7.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Pigment red 202, Propylene carbonate, Quinacridone pigment, Toluene(4%*), Vm&p naphtha, Xylene(29%*)

GAL WT: 8.04 WT PCT SOLIDS: 38.95 VOL PCT SOLIDS: 31.34
SOLVENT DENSITY: 7.16 VOC LE: 4.9 VOC AP: 4.9
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

727A™ Acrylic polymer-B, Alkyd resin, Aluminum(3%*), Aromatic hydrocarbon-A, Ethylbenzene(2.6%*), Medium mineral spirits, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(37%*), Xylene(10%*)

GAL WT: 8.09 WT PCT SOLIDS: 42.03 VOL PCT SOLIDS: 34.69
SOLVENT DENSITY: 7.18 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

728A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, C.i. pigment blue 15 (monochlor), Ethylbenzene(7.8%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine blue pigment, Toluene(7%*), Vm&p naphtha, Xylene(30%*)

GAL WT: 8.00 WT PCT SOLIDS: 40.12 VOL PCT SOLIDS: 33.02
SOLVENT DENSITY: 7.15 VOC LE: 4.8 VOC AP: 4.8
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

731A™ Acrylic polymer-B, Alkyd resin, Antimony trioxide(0.5%*), Aromatic hydrocarbon-A, Barium sulfate, Butyl acetate, Ethylbenzene(4.2%*), Lead chromate molybdate(16.3%*), Lead chromate oxide(0.8%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(11%*), Vm&p naphtha, Xylene(17%*)

GAL WT: 9.54 WT PCT SOLIDS: 54.55 VOL PCT SOLIDS: 38.49
SOLVENT DENSITY: 7.03 VOC LE: 4.3 VOC AP: 4.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

732A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(5.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(7%*), Vm&p naphtha, Xylene(21%*), Yellow iron oxide

GAL WT: 8.72 WT PCT SOLIDS: 48.15 VOL PCT SOLIDS: 35.36
SOLVENT DENSITY: 7.00 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

733A™ Acrylic polymer-B, Alkyd resin, Antimony trioxide(0.1%*), Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(4.4%*), Lead chromate molybdate(17.9%*), Lead chromate oxide(0.9%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(10%*), Vm&p naphtha, Xylene(18%*)

GAL WT: 9.42 WT PCT SOLIDS: 52.98 VOL PCT SOLIDS: 37.09
SOLVENT DENSITY: 7.02 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

734A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Dioxazine carbozole pigment, Ethylbenzene(7.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(9%*), Vm&p naphtha,

Xylene(31%*)

GAL WT: 7.78 WT PCT SOLIDS: 35.60 VOL PCT SOLIDS: 28.91
SOLVENT DENSITY: 7.07 VOC LE: 5.0 VOC AP: 5.0
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

736A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(5.5%*), Isoindolinone pigment-B, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(13%*), Vm&p naphtha, Xylene(22%*)

GAL WT: 8.04 WT PCT SOLIDS: 45.09 VOL PCT SOLIDS: 37.34
SOLVENT DENSITY: 7.03 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

737A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(3.2%*), Lead chromate oxide(21.6%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(11%*), Vm&p naphtha, Xylene(13%*)

GAL WT: 9.56 WT PCT SOLIDS: 54.74 VOL PCT SOLIDS: 38.13
SOLVENT DENSITY: 6.98 VOC LE: 4.3 VOC AP: 4.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

738A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(4.4%*), Lead chromates(8.6%*), Methyl ethyl ketone, Naphthalene(0.2%*), Titanium dioxide(0.2%), Toluene(10%*), Vm&p naphtha, Xylene(18%*)

GAL WT: 9.08 WT PCT SOLIDS: 50.66 VOL PCT SOLIDS: 36.09
SOLVENT DENSITY: 6.99 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

741A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(7.0%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine green pigment, Toluene(10%*), Vm&p naphtha, Xylene(27%*)

GAL WT: 8.01 WT PCT SOLIDS: 42.12 VOL PCT SOLIDS: 34.71
SOLVENT DENSITY: 7.10 VOC LE: 4.6 VOC AP: 4.6
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

742A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(6.2%*), Methyl ethyl ketone, Naphthalene(0.1%*), Phthalocyanine green, Toluene(8%*), Vm&p naphtha, Xylene(24%*)

GAL WT: 7.94 WT PCT SOLIDS: 41.22 VOL PCT SOLIDS: 33.55
SOLVENT DENSITY: 7.02 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

746A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(5.9%*), Methyl ethyl ketone, Naphthalene(0.1%*), Quinacridone pigment, Toluene(8%*), Vm&p naphtha, Xylene(24%*)

GAL WT: 7.98 WT PCT SOLIDS: 43.29 VOL PCT SOLIDS: 35.50
SOLVENT DENSITY: 7.01 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

747A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(8.1%*), Methyl ethyl ketone, Naphthalene(0.1%*), Quinacridone magenta, Quinacridone pigment, Toluene(4%*), Xylene(32%*)

GAL WT: 8.06 WT PCT SOLIDS: 41.23 VOL PCT SOLIDS: 34.32
SOLVENT DENSITY: 7.21 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

748A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl

acetate, Ethylbenzene(5.7%*), Methyl ethyl ketone, Naphthalene(0.1%*), Quinacridone pigment, Toluene(10%*), Vm&p naphtha, Xylene(23%*)

GAL WT: 7.91 WT PCT SOLIDS: 42.76 VOL PCT SOLIDS: 35.44
SOLVENT DENSITY: 7.01 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

749A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(6.3%*), Methyl ethyl ketone, Naphthalene(0.3%*), Perylene pigment, Toluene(11%*), Vm&p naphtha, Xylene(25%*)
GAL WT: 7.94 WT PCT SOLIDS: 40.27 VOL PCT SOLIDS: 32.76
SOLVENT DENSITY: 7.05 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

750A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(7.2%*), Iron oxide-B, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(7%*), Vm&p naphtha, Xylene(28%*)
GAL WT: 8.15 WT PCT SOLIDS: 41.80 VOL PCT SOLIDS: 32.93
SOLVENT DENSITY: 7.08 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

752A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(4.9%*), Iron oxide-A, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(4%*), Vm&p naphtha, Xylene(19%*)
GAL WT: 8.28 WT PCT SOLIDS: 40.04 VOL PCT SOLIDS: 30.04
SOLVENT DENSITY: 7.10 VOC LE: 5.0 VOC AP: 5.0
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

756A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Ethylbenzene(7.6%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(12%*), Vm&p naphtha, Xylene(30%*)
GAL WT: 7.88 WT PCT SOLIDS: 39.10 VOL PCT SOLIDS: 32.64
SOLVENT DENSITY: 7.12 VOC LE: 4.8 VOC AP: 4.8
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

758S™ Butyl acetate, Cobalt naphthenate(3.7%*), Ethylbenzene(0.6%*), Medium mineral spirits, Toluene(10%*), Vm&p naphtha, Xylene(2%*), Zirconium octoate
GAL WT: 6.88 WT PCT SOLIDS: 5.80 VOL PCT SOLIDS: 4.05
SOLVENT DENSITY: 6.75 VOC LE: 6.5 VOC AP: 6.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

761A™ Acrylic polymer-B, Alkyd resin, Antimony(9%*), Aromatic hydrocarbon-A, Butyl acetate, Chromium(iii)(4%*), Ethylbenzene(6.1%*), Methyl ethyl ketone, Naphthalene(0.2%*), Titanium dioxide (rutile)(7.8%), Toluene(4%*), Vm&p naphtha, Xylene(23%*)
GAL WT: 9.63 WT PCT SOLIDS: 54.76 VOL PCT SOLIDS: 39.30
SOLVENT DENSITY: 7.18 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

762A™ Acrylic polymer-B, Alkyd resin, Antimony pentoxide(3%*), Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(5.4%*), Methyl ethyl ketone, Naphthalene(0.1%*), Nickel oxide(1.0%*), Titanium dioxide(16.4%), Toluene(7%*), Vm&p naphtha, Xylene(22%*)
GAL WT: 9.46 WT PCT SOLIDS: 54.63 VOL PCT SOLIDS: 39.49
SOLVENT DENSITY: 7.09 VOC LE: 4.3 VOC AP: 4.3
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

763A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, Ethylbenzene(6.6%*), Monoazo pigment,

Naphthalene(0.3%*), Toluene(3%*), Vm&p naphtha, Xylene(26%*)
GAL WT: 8.29 WT PCT SOLIDS: 45.05 VOL PCT SOLIDS: 36.07
SOLVENT DENSITY: 7.14 VOC LE: 4.6 VOC AP: 4.6
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

764A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Butyl acetate, C.i. pigment yellow 154, Ethylbenzene(7.5%*), Methyl ethyl ketone, Naphthalene(0.1%*), Titanium dioxide(0.1%), Toluene(4%*), Vm&p naphtha, Xylene(28%*)
GAL WT: 8.20 WT PCT SOLIDS: 45.00 VOL PCT SOLIDS: 36.79
SOLVENT DENSITY: 7.13 VOC LE: 4.5 VOC AP: 4.5
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

765A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Barium sulfate, Butyl acetate, Ethylbenzene(4.0%*), Isoindolinone pigment-A, Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(9%*), Vm&p naphtha, Xylene(16%*)
GAL WT: 8.67 WT PCT SOLIDS: 49.21 VOL PCT SOLIDS: 37.70
SOLVENT DENSITY: 7.05 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

767A™ Acrylic polymer-B, Alkyd resin, Aromatic hydrocarbon-A, Azo yellow pigment, Butyl acetate, Ethylbenzene(4.2%*), Methyl ethyl ketone, Naphthalene(0.1%*), Toluene(12%*), Vm&p naphtha, Xylene(17%*)
GAL WT: 8.20 WT PCT SOLIDS: 46.82 VOL PCT SOLIDS: 37.99
SOLVENT DENSITY: 7.02 VOC LE: 4.4 VOC AP: 4.4
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

2000S-A™ 1,2,4-trimethyl benzene(3%*), 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate, Aromatic hydrocarbon-B, Polyester resin-B, Polyethylene glycol diethyl hexoate, Toluene(31%*)
GAL WT: 7.93 WT PCT SOLIDS: 39.92 VOL PCT SOLIDS: 36.30
SOLVENT DENSITY: 7.46 VOC LE: 4.8 VOC AP: 4.8
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

8105S™ 4,6-dimethyl-2-heptanone, Aliphatic polyisocyanate resin, Aromatic hydrocarbon-A, Aromatic hydrocarbon-B, Butyl acetate, Diisobutyl ketone, Ethylbenzene(2.3%*), Naphthalene(0.8%*), Xylene(9%*)
GAL WT: 8.12 WT PCT SOLIDS: 41.96 VOL PCT SOLIDS: 34.91
SOLVENT DENSITY: 7.23 VOC LE: 4.7 VOC AP: 4.7
FLASH POINT: 73°F to below 100°F H: 3 F: 3 R: 1 OSHA STORAGE: IC
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

8165S™ Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate, Butyl acetate, Ethyl 3-ethoxy propionate, Ethyl acetate, Ethylbenzene(0.6 - 1.5%*), Polyester resin-A, Substituted benzotriazole, Toluene(17 - 17%*), Vm&p naphtha, Xylene(4 - 5%*)
GAL WT: 7.78 WT PCT SOLIDS: 35.50 VOL PCT SOLIDS: 30.33
SOLVENT DENSITY: 7.18 VOC LE: 5.0 VOC AP: 5.0
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

8170S™ Acetone, Acrylic polymer-A, Butyl acetate, Castor oil, dehydrated, Ethanol, 2-(2-butoxyethoxy)-(6%*), Ethyl 3-ethoxy propionate, Ethylbenzene(2.9%*), Methyl amyl ketone, Vm&p naphtha, Xylene(12%*)
GAL WT: 7.46 WT PCT SOLIDS: 28.81 VOL PCT SOLIDS: 24.63
SOLVENT DENSITY: 7.02 VOC LE: 5.3 VOC AP: 5.0
FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

8175S™ Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate, Butyl acetate, Ethanol, 2-(2-butoxyethoxy)-(7%*), Ethyl 3-ethoxy propionate,

Ethylbenzene(1.2%* @), Polyester resin-A, Substituted benzotriazole,
Vm&p naphtha, Xylene(5%* @)

GAL WT: 7.69 WT PCT SOLIDS: 35.49 VOL PCT SOLIDS: 29.97

SOLVENT DENSITY: 7.05 VOC LE: 5.0 VOC AP: 5.0

FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB

TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

8180S™ 1,2,4-trimethyl benzene(3%*), Acrylic polymer-A, Aromatic hydrocarbon-A, Aromatic hydrocarbon-B, Butyl acetate, Castor oil, dehydrated, Ethylbenzene(1.9%* @), Ethylene glycol monobutyl ether acetate(6%* @), Methyl amyl ketone, Naphthalene(0.4%* @), Oxo-octyl acetate, Vm&p naphtha, Xylene(8%* @)

GAL WT: 7.54 WT PCT SOLIDS: 28.80 VOL PCT SOLIDS: 24.88

SOLVENT DENSITY: 7.13 VOC LE: 5.4 VOC AP: 5.4

FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB

TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

8185S™ Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate, Butyl acetate, Ethanol, 2-(2-butoxyethoxy)-(7%* @), Ethyl 3-ethoxy propionate, Ethylbenzene(1.2%* @), Ethylene glycol monobutyl ether acetate(11%* @), Polyester resin-A, Substituted benzotriazole, Vm&p naphtha, Xylene(5%* @)

GAL WT: 7.90 WT PCT SOLIDS: 35.48 VOL PCT SOLIDS: 30.77

SOLVENT DENSITY: 7.34 VOC LE: 5.1 VOC AP: 5.1

FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB

TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

8195S™ Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate, Butyl acetate, Ethanol, 2-(2-butoxyethoxy)-(4%* @), Ethyl 3-ethoxy propionate, Ethylbenzene(0.6 - 1.5%* @), Ethylene glycol monobutyl ether acetate(16%* @), Polyester resin-A, Substituted benzotriazole, Vm&p naphtha, Xylene(4 - 5%* @)

GAL WT: 7.94 WT PCT SOLIDS: 35.49 VOL PCT SOLIDS: 30.94

SOLVENT DENSITY: 7.39 VOC LE: 5.1 VOC AP: 5.1

FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 1 OSHA STORAGE: IB

TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO

Footnotes:

TSCA: in compliance = In compliance with TSCA Inventory requirements for commercial purposes.

ACGIH = American Conference of Governmental Industrial Hygienists.

IARC = International Agency for Research on Cancer.

NTP = National Toxicology Program.

OSHA = Occupational Safety and Health Administration.

PNOR = Particles not otherwise regulated.

PNOC = Particles not otherwise classified.

STEL = Short term exposure limit.

TWA = Time-weighted average.

TM = Is a Trademark of E.I. DuPont de Nemours Co.

* = Section 313 Supplier Notification: These chemicals are subject to the reporting requirements of Section 313 of the Emergency planning and Right-to-Know act of 1986 and of 40 CFR 372.

@ = Listed as a Clean Air Act Hazardous Air Pollutant.

= EPCRA Section 302 - Extremely hazardous substances.

Notice:

The information on this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Product Manager: Refinish Sales

Prepared by: Y. B. Yarbrough