



Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

1 Identification of substance

HMG

· Product details**· Trade name:** Microshield/Aluma-Protect 102 Topcoat**· Article number:**

3581

Stock Code:2040

· Application of the substance / the preparation Coating compound/ Surface coating/ paint**· Manufacturer/Supplier:**

HMG AMERICA LLC,

PO BOX313

ROEBUCK

SC29376

TEL 864 585 0266

FAX 864 585 3808

· Information department: CHEMTREC 1-800 424 9300 or 1(703)527 3887 outside the USA

2 Composition/Data on components

· Chemical characterization**· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:**

64742-94-5	Solvent naphtha (petroleum), heavy arom.	25-50%
	Aliphatic Polyisocyanate	25-50%
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%
123-86-4	n-butyl acetate	£ 2.5%
95-63-6	1,2,4-trimethylbenzene	£ 2.5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· Hazard description:

Harmful

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

May cause sensitization by skin contact.

Harmful: may cause lung damage if swallowed.

Contains isocyanates. See information supplied by the manufacturer.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002


Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 1)

· **NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 2
Reactivity = 0

· **WHMIS-ratings (scale 0 - 4)**

Health = 2
Fire = 2
Reactivity = 0

4 First aid measures

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** No special measures required.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 2)

· Class according to regulation on flammable liquids: A II

8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· General Information

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 160°C (320°F)

· Flash point: 41°C (106°F)

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 3)

· Ignition temperature:	450.0°C (842°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20°C (68°F):	5.0 hPa
· Density:	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions:** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant.

12 Ecological information

- **General notes:** Not known to be hazardous to water.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 4)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



- **Hazard class:** -
- **Identification number:** UN1263
- **Proper shipping name (technical name):** Paint related material

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 Flammable liquids
- **Item:** 31c
- **Danger code (Kemler):** 90
- **UN-Number:** 1263
- **Description of goods:** 1263 Paint related material

· **Maritime transport IMDG:**

- **IMDG Class:** -
- **UN Number:** 1263
- **Marine pollutant:** No
- **Proper shipping name:** Paint

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** -
- **UN/ID Number:** 1263
- **Proper shipping name:** Paint

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

95-63-6 1,2,4-trimethylbenzene

· **TSCA (Toxic Substances Control Act):**

64742-94-5 Solvent naphtha (petroleum), heavy arom.

64742-95-6 Solvent naphtha (petroleum), light arom.

123-86-4 n-butyl acetate

95-63-6 1,2,4-trimethylbenzene

141-78-6 ethyl acetate

4083-64-1 4-isocyanatosulphonyltoluene

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 5)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

77-58-7 dibutyltin dilaurate A4

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Harmful

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), heavy arom.

Aliphatic Polyisocyanate

Solvent naphtha (petroleum), light arom.

· Risk phrases:

May cause sensitization by skin contact.

Harmful: may cause lung damage if swallowed.

· Safety phrases:

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin.

Wear suitable gloves.

This material and its container must be disposed of as hazardous waste.

· Special labeling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer.

· National regulations:

· Classification according to VbF: A II

(Contd. on page 7)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 08/06/2002

Reviewed on 05/31/2000

Trade name: Microshield/Aluma-Protect 102 Topcoat

(Contd. of page 6)

· Technical instructions (air):

Class	Share in %
<i>II</i>	13.8
<i>III</i>	2.5

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department: LABORATORY

· Contact: DAVE MCROBBIE

USA