

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

### 1 Identification of substance

HMG

- **Product details**
- **Trade name:** Superspeed SP52 Reducer
- **Article number:** 1122
- **Application of the substance / the preparation** Coating compound/ Surface coating/ paint
- **Manufacturer/Supplier:**  
HMG AMERICA LLC,  
PO BOX313  
ROEBUCK  
SC29376  
TEL 864 578 6770  
FAX 864 578 6770
- **Information department:** CHEMTREC 1-800 424 9300 or 1(703)527 3887 outside the USA

### 2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

108-65-6	2-methoxy-1-methylethyl acetate	25-50%
108-10-1	4-methylpentan-2-one	25-50%
95-63-6	1,2,4-trimethylbenzene	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%
103-65-1	propylbenzene	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 3 Hazards identification

· **Hazard description:**



Harmful  
Highly flammable  
Dangerous for the environment

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Highly flammable.

Harmful by inhalation.

Irritating to eyes and respiratory system.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Harmful: may cause lung damage if swallowed.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

Trade name: **Superspeed SP52 Reducer**

(Contd. of page 1)

108-10-1	4-methylpentan-2-one
95-63-6	1,2,4-trimethylbenzene

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

· **WHMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

## 4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

## 5 Fire fighting measures

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** Mount respiratory protective device.

## 6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:**

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

USA

(Contd. on page 3)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

Trade name: *Superspeed SP52 Reducer*

(Contd. of page 2)

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Keep receptacles tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 108-10-1 4-methylpentan-2-one

PEL	410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
BEI	

### 95-63-6 1,2,4-trimethylbenzene

REL	125 mg/m <sup>3</sup> , 25 ppm
TLV	123 mg/m <sup>3</sup> , 25 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

**Trade name: Superspeed SP52 Reducer**

(Contd. of page 3)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Fluid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 114°C (237°F)

· **Flash point:** 17°C (63°F)

· **Ignition temperature:** 315.0°C (599°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	10.8 Vol %

· **Vapor pressure at 20°C (68°F):** 8.0 hPa (6 mm Hg)

· **Density at 20°C (68°F):** 0.890 g/cm<sup>3</sup>

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Solvent content:**

**Organic solvents:** 98.0 %

## 10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous products of decomposition:** No dangerous decomposition products known.

USA

(Contd. on page 5)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

Trade name: *Superspeed SP52 Reducer*

(Contd. of page 4)

## 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**108-10-1 4-methylpentan-2-one**

Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

## 12 Ecological information

- **Ecotoxicological effects:**

- **Remark:** Toxic for fish

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## 13 Disposal considerations

- **Product:**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **DOT regulations:**



- **Hazard class:**

3

- **Identification number:**

UN1263

(Contd. on page 6)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

Trade name: *Superspeed SP52 Reducer*

(Contd. of page 5)

- **Packing group:** II
- **Proper shipping name (technical name):** PAINT
- **Label** 3

- **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 Flammable liquids
- **Danger code (Kemler):** 33
- **UN-Number:** 1263
- **Packaging group:** II
- **Description of goods:** 1263 PAINT

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** PAINT

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** PAINT

## 15 Regulations

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

(Contd. on page 7)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/21/2004

Reviewed on 07/21/2004

**Trade name: Superspeed SP52 Reducer**

(Contd. of page 6)

· **Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful

Highly flammable

Dangerous for the environment

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light arom.

4-methylpentan-2-one

· **Risk phrases:**

Highly flammable.

Harmful by inhalation.

Irritating to eyes and respiratory system.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Use appropriate container to avoid environmental contamination.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	98.0

(Contd. on page 8)

USA

**Material Safety Data Sheet**  
*acc. to ISO/DIS 11014*

Printing date 07/21/2004

Reviewed on 07/21/2004

**Trade name: Superspeed SP52 Reducer**

(Contd. of page 7)

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing MSDS:** Product safety department: LABORATORY
- **Contact:** DAVE MCROBBIE

USA